

For the ultimate in electric, hot water pressure washers, opt for this belt drive unit that offers larger volume capacity and quiet operation.

HSE Series

PORTABLE

ELECTRIC - BELT DRIVE



HSE-3504-OM10

Pump: Belt drive triplex piston General pump with ceramic plungers • Stainless-steel and brass unloader valve • Forged brass manifold • Thermal relief valve • High pressure detergent injection

Motor: Totally enclosed fan-cooled electric motor with manual thermal overload protection • 35-foot power cord (ground fault circuit interrupter on HSE-2504-OM10)

Frame: Reinforced powder coated steel tube frame with center balanced lifting hook • Powder coated steel hose reel mounting bracket • Electric cord hanger • Powder coated steel gun/wand holder • Solid steel threaded axles • Pneumatic tires with tubes (4) • Locking tire brake

Components: Complete system diagnostic board • Float tank • Pressure and high limit safety controls • No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time) • Polyethylene burner fuel tank • Easy coil drain helps prevent freezing in cold weather • Electrodes are self-gapping for proper ignition and combustion

Accessories: 50-foot x 3/8-inch steel wire-braided pressure hose with screw connects, swivel and bend restrictors • Professional-grade insulated trigger gun with safety lock-off • Adjustable pressure insulated dual lance with 15-degree fixed and detergent nozzle

Miscellaneous: Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Hot Water Pressure Washers



High quality fuel filter/water separator ensures clean fuel supply



Energy-efficient top-fired powder coated heat exchanger designed for convenient troubleshooting and easy maintenance



Heavy-duty dual cogged belt drive system to prevent slippage

Model No.	PSI	GPM	HP/Motor	Plug Type	Burner Fuel Tank Cap.	Burner Fuel Cons.	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HSE-2504-OM10	2500	3.2	6.0/230V, 1Ø, 25.0A	NEMA L6-30P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	699 lbs.	569 lbs.
HSE-2504-OM30	2500	3.2	6.0/230-460V, 3Ø, 16.0A	NEMA L15-20P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	688 lbs.	558 lbs.
HSE-3004-OM10	3000	3.5	8.0/230V, 1Ø, 36.0A	NEMA 6-50P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	737 lbs.	607 lbs.
HSE-3004-OM30	3000	3.5	8.0/230-460V, 3Ø, 24.0A	NEMA L15-30P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	732 lbs.	602 lbs.
HSE-3504-OM10	3500	3.3	10.0/230V, 1Ø, 39.0A	NEMA 6-50P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	761 lbs.	631 lbs.
HSE-3504-OM30	3500	3.3	10.0/230-460V, 3Ø, 28.0A	NEMA L15-30P	10.0 gallon	2.10 gph	49.5in.x28in.x40.5in.	742 lbs.	612 lbs.



NEMA L15-20P, 20-amp plug



NEMA L15-30P, 30-amp plug



NEMA L6-30P, 30-amp plug



NEMA 6-50P, 50-amp plug

Options (Consult price list or www.mitm.com for more information on option descriptions and qualifying models)

- HX-0070 Auto start/stop
- HX-0071 - HX-0073 Auto start/stop-steam
- HX-0074 Auto start/stop-CAD cell
- HX-0075 - HX-0077 Auto start/stop-steam/CAD cell
- HX-0085 - HX-0087 460V
- HX-0088 Skid feet
- HX-0161 Hour meter
- TX-1304-W Puncture-proof tires

1 YEAR LIMITED
ELECTRIC MOTOR WARRANTY

2 YEAR LIMITED
PARTS & LABOR WARRANTY



3 YEAR LIMITED
COIL WARRANTY

7 YEAR LIMITED
PUMP WARRANTY