

JP Series

Optimal balance and maneuverability represent just a few of the great benefits the JP Series offers with its extended handle design. The Mi-T-M quality and durability you've come to expect also shines through with its 1-inch mild steel construction.

GASOLINE - DIRECT DRIVE

PORTABLE

2 NEW Models

Cold Water Pressure Washers



JP-2703-0MHB

Pump: Direct drive triplex piston AR or Mi-T-M pump with ceramic plungers • Stainless-steel and brass unloader • Adjustable pressure • Forged brass manifold • Thermal relief valve • In-line water strainer


Engine: Performance-proven engine with low-oil protection

Frame: Solid steel axle (threaded on 3000- to 4000-PSI models) • Pneumatic tires with tubes for longer life • Dual rubber isolators

Accessories: Quick connect nozzles (0°, 15° and 25°) • 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors • Professional-grade insulated trigger gun with safety lock-off • 36-inch lance with rubber grip (48-inch lance on 3500- & 4000-PSI models)



1-inch powder coated steel tube handle for easier pulling



3/16-inch powder coated and welded steel base plate



Convenient gun/wand holder and hose wrap

Model No.	PSI	GPM	Displacement*/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JP-2403-0MHB	2400	2.4	196cc Honda OHV	37in.x21in.x24.5in.	100 lbs.	75 lbs.
JP-2403-0MRB	2400	2.4	211cc Subaru OHC	37in.x21in.x24.5in.	100 lbs.	75 lbs.
JP-2703-0MHB	2700	2.4	196cc Honda OHV	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-2703-0MRB	2700	2.4	211cc Subaru OHC	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-2703-8MHB	2700	2.4	196cc Honda OHV	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-2703-8MRB	2700	2.4	211cc Subaru OHC	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-3003-0MHB	3000	3.0	270cc Honda OHV	40in.x22.5in.x24.5in.	180 lbs.	130 lbs.
JP-3003-0MRB	3000	3.0	265cc Subaru OHC	40in.x22.5in.x24.5in.	180 lbs.	130 lbs.
JP-3004-0MHB	3000	3.5	389cc Honda OHV	40in.x22.5in.x24.5in.	186 lbs.	136 lbs.
JP-3504-0MHB	3500	3.5	389cc Honda OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-3504-0MRB	3500	3.5	404cc Subaru OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-4004-1MHB	4000	3.5	389cc Honda OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-4004-1MRB	4000	3.5	404cc Subaru OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.

*As rated by engine manufacturer.

Options (Consult price list or www.mitm.com for more information on option descriptions and qualifying models)

50-0161 High pressure detergent injection
 AW-8400-0021 Low pressure detergent injection
 CX-0005 Insulated dual lance
 TX-1002-W Puncture-proof tires

NEW!

1 YEAR LIMITED PARTS & LABOR WARRANTY

2 YEAR LIMITED HONDA ENGINE WARRANTY

2 YEAR LIMITED MI-T-M PUMP WARRANTY

3 YEAR LIMITED SUBARU ENGINE WARRANTY

7 YEAR LIMITED AR PUMP WARRANTY

Certified to UL-1776

The powerful electric, direct-drive JP Series is the perfect selection for indoor applications, providing a quiet, exhaust-free operation.

JP Series

PORTABLE

ELECTRIC - DIRECT DRIVE



JP-2003-1ME1

Pump: Direct drive triplex piston General or AR pump with ceramic plungers • Stainless-steel and brass unloader • Adjustable pressure • Forged brass manifold • Thermal relief valve • Safety relief valve • In-line water strainer • Adjustable low pressure detergent injection

Motor: Totally enclosed fan-cooled electric motor • 35-foot power cord (ground fault circuit interrupter, GFCI, on 1.5- to 6.0-HP single-phase models) • NEMA 5-20P, 20-amp plug (1500-PSI models)

Frame: Solid steel axle (threaded on 2000- to 3000-PSI models) • Pneumatic tires with tubes for longer life • Dual rubber isolators

Accessories: Variable high/low pressure nozzle (1000- to 2000-PSI models) • Quick connect nozzles (0°, 15° and 25°) (2500- & 3000-PSI models) • 25-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors • Professional-grade insulated rubber trigger gun with safety lock-off • 36-inch lance with rubber grip

Cold Water Pressure Washers



1-inch powder coated steel tube handles for easier pulling



3/16-inch powder coated and welded steel base plate



Convenient gun/hose wrap and hose wrap

Model No.	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JP-1002-0ME1 ^{*A#}	1000	2.0	1.5/120V, 1Ø, 15.0A	NEMA 5-15P	37in.x21in.x24.5in.	120 lbs.	90 lbs.
JP-1002-2ME1 ^{*A#+}	1000	2.0	1.5/120V, 1Ø, 15.0A	NEMA 5-15P	37in.x21in.x24.5in.	120 lbs.	90 lbs.
JP-1502-0ME1 ^{*A#}	1500	2.0	2.0/120V, 1Ø, 20.0A	NEMA 5-20P	37in.x21in.x24.5in.	120 lbs.	90 lbs.
JP-1502-2ME1 ^{*A#+}	1500	2.0	2.0/120V, 1Ø, 20.0A	NEMA 5-20P	37in.x21in.x24.5in.	120 lbs.	90 lbs.
JP-2003-1ME1 ^{*A#}	2000	2.8	4.0/230V, 1Ø, 16.0A	NEMA L6-20P	37in.x21in.x24.5in.	162 lbs.	112 lbs.
JP-2503-1ME1 ^{*A}	2500	3.2	6.0/230V, 1Ø, 24.1A	NEMA L6-30P	44in.x26in.x27in.	275 lbs.	225 lbs.
JP-2503-0ME3	2500	3.2	6.0/230V, 3Ø, 15.0A or 6.0/460V, 3Ø, 7.5A	NEMA L15-20P	44in.x26in.x27in.	275 lbs.	225 lbs.
JP-3004-1ME1 ^A	3000	3.9	8.0/230V, 1Ø, 34.5A	NEMA 6-50P	44in.x26in.x27in.	275 lbs.	225 lbs.
JP-3004-0ME3	3000	3.9	8.0/230V, 3Ø, 20.0A or 8.0/460V, 3Ø, 10.0A	NEMA L15-30P	44in.x26in.x27in.	275 lbs.	225 lbs.



NEMA 5-15P, 15-amp plug



NEMA 5-20P, 20-amp plug



NEMA L15-20P, 20-amp plug



NEMA L6-20P, 20-amp plug



NEMA L15-30P, 30-amp plug



NEMA L6-30P, 30-amp plug



NEMA 6-50P, 50-amp plug

^{*}35-foot cord with ground fault circuit interrupter (GFCI).

^ASingle-phase models are CSA certified.

[#]Models are equipped with General pumps, all other models are equipped with AR pumps.

⁺Pump accepts incoming water up to 180-degrees.

Options (Consult price list or www.mitm.com for more information on option descriptions and qualifying models)

50-0161	High pressure detergent injection
CX-0005	Insulated dual lance
CX-0030	50-foot high pressure hose
CX-0066, CX-0067	460V on 6.0- & 8.0-HP, 3-phase models
TX-1002-W	Puncture-proof tires
TX-1302-W	Puncture-proof tires

1 YEAR LIMITED

PARTS & LABOR WARRANTY

1 YEAR LIMITED

ELECTRIC MOTOR WARRANTY

7 YEAR LIMITED

PUMP WARRANTY



Certified in USA & Canada:
JP-1002, JP-1502
Single Phase Models



Certified in USA Only:
JP-2003, JP-2503,
JP-3004 Single Phase Models